



Knowledge Beyond Measure.

# OmniTrak™ Solution Modules



## Efficiency Meets Intelligence. Customizable, Scalable, and Affordable Monitoring.

The OmniTrak™ SmartStation can be used in conjunction with any OmniTrak™ module to provide immediate feedback as to the conditions in the immediate area. Take measurements, create reports, and analyze data provided to help improve conditions.

This instrument is a handheld device, not to be worn on the body, or near an individual's head.

Smart Station	7590-00
VOC-PID ppb Module	7591-03
CO Module	7591-06
CI Module	7591-10
HCHO Module	7591-07
O <sub>3</sub> Module	7591-08
NH <sub>3</sub> Module	7591-11
VOC-PID ppm Module	7591-02
PM Module	7591-01
PM + VOC-PID ppm Module	7591-04

### Features and Benefits

- Wireless connection for up to 10 modules simultaneously
- Large touch-screen with intuitive navigation used for recording studies, managing data, viewing historical data, real-time measurements, etc.
- Download data directly from the device onto your PC or uploaded data to our TSI Link™ cloud platform to manage and view data remotely
- Unique laser-based light scattering particle sensors – outputs mass concentration data (PM1, PM2.5, PM4, PM10) and particle number concentration data separated into 5 distinct bins
- Precise 10.6 eV PID (photo ionization detector) for monitoring various VOCs (volatile organic compounds) in the PPM range
- Modular design allowing for flexibility and connection to future next generation modules

### Applications

- Portable/fixed air filter and air purifier verification
- Ventilation effectiveness testing
- IAQ studies in commercial/residential buildings, schools, hospitals, industrial manufacturing, etc.
- Industrial/occupational hygiene surveys and indoor air quality investigations
- Engineering control evaluations



## Module Sensor Specifications

Sensor Model	Sensor Type	Range	Accuracy	Resolution	*Response Time
VOC-PID (PPB) Module <b>Model 7591-03</b>	PID (Photo Ionization Detector)	0-20000 ppb	—	1 ppb	15 seconds
Carbon Monoxide (CO) Module <b>Model 7591-06</b>	Electrochemical	0- 400 ppm	15% + 2 ppm	0.1 ppm	45 seconds
Chlorine (Cl <sub>2</sub> ) Module <b>Model 7591-10</b>	Electrochemical	0- 20 ppm	5% + 0.8 ppm	0.01 ppm	90 seconds
Formaldehyde (HCHO) Module <b>Model 7591-07</b>	Electrochemical	0- 10 ppm	2% + 1 ppm	0.01 ppm	300 seconds
Ozone (O <sub>3</sub> ) Module <b>Model 7591-08</b>	Electrochemical	0- 20 ppm	15% + 1.5 ppm	0.01 ppm	60 seconds
Ammonia (NH <sub>3</sub> ) Module <b>Model 7591-11</b>	Electrochemical	0- 100 ppm	+/- 10 ppm	0.1 ppm	15 seconds

Measurement specifications apply at ambient conditions of 21 +/- 5 °C temperature, 98.6 +/- 5 kPa pressure, and 50 +/- 10% relative humidity.

\* (Typical) time to 90% of final value

Sensor Model	Sensor Type	Ionization Energy (PID Lamp electron voltage)	Concentration Range	Resolution	*Response Time
VOC Modules <b>Models: 7591-02 VOC-PID (ppm) Module, 7591-04 PM + VOC-PID (ppm) Module</b>	PID (Photo Ionization Detector)	10.6 eV	0-2000 ppm	0.1 ppm	<10 seconds

Measurement specifications apply at ambient conditions of 21 +/- 5 °C temperature, 98.6 +/- 5 kPa pressure, and 50 +/- 10% relative humidity.

## PM Sensor Specifications

### PM Modules

**Models: 7591-01 PM Module, 7591-04 PM + VOC-PID (ppm) Module**

Particle Counter			
Concentration Range	0 to 3,000 (0 to 84,950,000)	—	#/cm <sup>3</sup> (#/ft <sup>3</sup> )
Particle Bins and Particle Size Range (NC = Number Concentration)	NC0.5	0.3 to 0.5	µm
	NC1.0	0.5 to 1.0	µm
	NC2.5	1.0 to 2.5	µm
	NC4	2.5 to 4.0	µm
	NC10	4.0 to 10.0	µm
Concentration Precision <sup>1</sup> for PM0.5, PM1, and PM2.5 <sup>2</sup>	0 to 1,000 #/cm <sup>3</sup> (0 to 28,320,000 #/ft <sup>3</sup> )	±100 (±2,832,000)	#/cm <sup>3</sup> (#/ft <sup>3</sup> )
	1000 to 3000 #/cm <sup>3</sup> (28,320,000 to 84,950,000 #/ft <sup>3</sup> )	±10	% m.v.
Concentration Precision <sup>1</sup> for PM4, PM10 <sup>3</sup>	0 to 1000 #/cm <sup>3</sup> (0 to 28,320,000 #/ft <sup>3</sup> )	±250 (±7,080,000)	#/cm <sup>3</sup> (#/ft <sup>3</sup> )
	1000 to 3000 #/cm <sup>3</sup> (28,320,000 to 84,950,000 #/ft <sup>3</sup> )	±25	% m.v.
Particulate Mass			
Concentration Range	0 to 1,000	—	µg/m <sup>3</sup>
Mass Concentration Bins and Particle Size Range	PM1.0	0.3 to 1.0	µm
	PM2.5	0.3 to 2.5	µm
	PM4.0	0.3 to 4.0	µm
	PM10.0	0.3 to 10.0	µm
Mass Concentration Precision <sup>1</sup> for PM1, and PM2.5 <sup>2</sup>	0 to 100 µg/m <sup>3</sup>	± [5 µg/m <sup>3</sup> + 5 % m.v.]	
	100 to 1000 µg/m <sup>3</sup>	±10	% m.v.
Mass Concentration Precision <sup>1</sup> for PM4, PM10 <sup>3</sup>	0 to 100 µg/m <sup>3</sup>	±25	µg/m <sup>3</sup>
	100 to 1000 µg/m <sup>3</sup>	±25	% m.v.

<sup>1</sup> Also referred to as "between-parts variation" or "device-to-device variation".

<sup>2</sup> Verification Aerosol for PM2.5 is a 3% atomized KCl solution. Deviation to reference instrument is verified in end-tests for every sensor after calibration.

<sup>3</sup> PM4 and PM10 output values are calculated based on distribution profile of all measured particles.

## Specifications

# OmniTrak™ Solution Modules

### Power Requirements \*

Input Power	10 W
Input Voltage	5 VDC
Charging Port	USB C

### Environmental/Installation Requirements \*

Maximum Altitude	3,000 m (10,000 ft)
Pollution Degree	2
Installation Category	I
Operating Temperature	5°C to 40°C
Storage Temperature	-20°C to 60°C
Humidity	0% to 95% (non-condensing)
BLE Range**	up to 100 m (328 ft)

### Battery Life

Modules	18 hrs.
Smart Station	14 hrs. (display brightness at 100%)

### Weight

Modules	.17 kg (.37 lbs)
Smart Station	.36 kg (.79 lbs)

### Dimensions

Modules	85 x 35 x 73 mm
Smart Station	85 x 35 x 175 mm

### Logging

Data Recording Interval	Every 1 sec
-------------------------	-------------

\* Applies to both Smart Station and Modules

\*\* Range is dependent on many variables (i.e. wireless traffic, metal, etc.) and can not be guaranteed.



Specifications are subject to change without notice.

Wi-Fi is a registered trademark by the Wi-Fi Alliance.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by [licensee name] is under license. Other trademarks and trade names are those of their respective owners.

TSI, the TSI logo are registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.



Distributed by:

Kenelec Scientific Pty Ltd  
1300 73 22 33  
sales@kenelec.com.au  
www.kenelec.com.au



**Knowledge Beyond Measure.**

TSI Incorporated - Visit our website [www.tsi.com](http://www.tsi.com) for more information.

<b>USA</b>	Tel: +1 800 874 2811	<b>India</b>	Tel: +91 80 67877200
<b>UK</b>	Tel: +44 149 4 459200	<b>China</b>	Tel: +86 10 8219 7688
<b>France</b>	Tel: +33 1 41 19 21 99	<b>Singapore</b>	Tel: +65 6595 6388
<b>Germany</b>	Tel: +49 241 523030		

